



# TECHNICAL DATA

**Backlit Coated Banner**  
**440g 500D\*500D**  
**28\*28**



Item	Data	Unit	Method
Yarn	500x500	Denier	DIN60001
Net structure	28x28	Thread / Inch	DIN53853
Net weight	100	g/sq.m	DIN53352
PVC film weight	350±10	g/sq.m	DIN53352
Product weight	440±10	g/sq.m	DIN53352
Thickness		mm	DIN53353
Products width	0.914-5.00	m	—
Tearing strength (L*W)	500x600	N/5cm	DIN53363
Tensile strength (L*W)	980x980	N/5cm	DIN53354
Elongation value (L*W)		%	DIN53354
Peeling strength	50x50	N/5cm	DIN53357
Color fastness	5	Level	ASTM D 1003
Temperature	-20~+60	°C	DIN53372
Expired time	6-12months		LM
Flame retardant	pass		DIN75200
Anti-wicking	without		—
Anti-frost	without		—
Anti-mildew	without		—
Acrylic lacquer	without		—
Applications	<p>JANEHONG backlit coated banner 440g 500D*500D 28*28 With excellent light transmittance and color expression, it is often used to make outdoor large-width light boxes and indoor light box advertisements. For example, internal lighting knives are often used to illuminate light boxes on the walls of shopping mall aisles to achieve high-rise image display.</p> <p>It optimized for Solvent, Eco-solvent, UV curable inkjet printer, such as VUTEK, NUR, HP SCITEX, EPSON, DGI, ROLAND, MUTOH, MIMAKI, ARIZONA, SALASA, TECKWIN, FLORA, INFINITI, etc</p>		

## Durability

Durability is based on field experience and exposure tests in China. Outdoor durability is 1 year when properly processed and applied (unprinted film vertical exposure).

## Shelf Life

Shelf life is 1 year from factory shipment.

## Storage Condition

Free from excessive moisture, temperature, direct sunlight (20°C x 50% R.H.).